

CALIPER

COMMERCIALLY AVAILABLE LED PRODUCT EVALUATION AND REPORTING PROGRAM

Ruth Taylor

Pacific Northwest National Laboratory

Market Introduction Workshop

Pittsburgh, PA July 17, 2012

Outline



CALIPER evolution

CALIPER process

Product performance

Next steps

How to use CALiPER reports and data

CALIPER Evolution



- CALIPER started in the SSL 'Wild Wild West'
 - No LM-79 test procedures
 - Little understanding of how to compare products
 - Many low efficacy products with even lower light output
 - Virtually no industry accountability
 - False equivalency claims by many
 - Potential for great consumer disappointment
- 2012 Entirely different story!

CALiPER's Emphasis



Historically:

- Capture market trends and gauge performance levels
- Improve manufacturer accountability
- Inspire consumer confidence

New Emphasis:

- Identify important areas for improvement
- Educate industry on potential issues
- Support standards activities

CALIPER Process



Product Selection & Purchasing

Independent LM-79-08 Testing

Data Analysis Report Publication

Step 1: Selection & Purchasing



I. Industry observations

- Website searches eLumit, DLC, LEDs magazine etc.
- Trade publications, popular media
- Manufacturer marketing materials
- Conventions, trade shows, and conferences
- National retailers

II. LED Lighting Facts quality assurance concerns

Do reported values reflect commercially available products?

III. CALiPER guidance committee

Manufacturers can't request tests or submit products.

Step 1: Selection Criteria



- Determine area of focus
- Select benchmark products
- Select products for reasonable comparisons
 - Lumen package
 - Color temperature
 - Color rendition
 - Product availability
 - Energy efficiency programs

Step 2: SSL Luminaire Testing



- Independent testing laboratories
- Uses absolute photometry rather than relative photometry (IES LM-79-08)
 - Must measure luminaire as a complete system
- Benchmark products for each application are also tested to LM-79
- Integrating sphere and goniophotometer testing



Photo credit: Luminaire Testing Laboratory

Step 3: Data Analysis



Key questions to answer:

- Does the product perform <u>as claimed?</u>
 - Marketing literature (equivalency and performance claims)
 - Specification sheets (at the time of the order)
 - Product packaging
- Does the product perform <u>as expected</u>?
 - What are you replacing?
 - What are you trying to accomplish?
 - How does the SSL product compare to conventional alternatives?









Summary Reports



- **2006** Pilot phase
 - 4 products (hard to purchase)
- **2007** Rounds 1-3
 - Small replacement lamps, desk lamps, undercabinet, small downlights
- **2008** Rounds 4-6
 - Downlight and T8 in situ testing, replacement lamps

- **2009** Rounds 7-9
 - Streetlights, bollards, downlights, 2x2 panels, 2x4 troffers, replacement lamps
- **2010** Rounds 10, 11
 - Parking garage, wallpack, cove lights, replacement lamps, roadway, high-bay
- **2011** Rounds 12, 13
 - Downlights, track lights, Alamps, T8 replacements, cove lights, high-bays, wall packs, 2x2 troffers

Upcoming Testing






How are Products Looking



- Overall improvements in light output, efficacy, light distribution, power factor, color quality
- Manufacturer claims are improving (LED Lighting Facts label helps) but equivalency claims can still be a problem
- Suitability often depends on application
 - Comparable products are now found in many lighting applications
 - Poor performing products are also found
- Careful comparisons based on accurate performance data is an absolute necessity
- Be cognizant of "secondary" quality issues: glare, flicker, color tolerances, physical formats, reliability...

CALIPER Process



CALIPER – Next Steps



- Industry 'snap shots' using LF data
- Application reports
 - New focus on specific applications and design scenarios
- Special Investigations
 - Expands application reports to incorporate product installations and evaluations
- Standards Support
 - Flicker, dimming, power quality testing


Using CALiPER Data



- Summary reports
 - Overall trends
 - Special considerations for focus application
 - Light output
 - Distribution
 - Color
 - LM-79 testing of benchmark products
- Detailed reports
 - Complete LM-79 report information online
 - Manufacturer claims for comparison


Summary Reports - Trends





Overall Trends - Efficacy






^{*}Includes both LED downlight retrofit units and integral LED downlights.


Overall Trends - Color








^{18 |} Solid-State Lighting Program


Comparing Distributions
























A-lamps

T-8 Replacements

Max=1464 cd
(outer circle)


SSL vs Fluorescent in
Parabolic Louvered






Visualizing Data


Metal Halide




versus LED





Understanding Color






Spectral Power Distribution Curve









Detailed Reports





Detailed Reports





| CALIPER RESULTS | | | MANUFACTURER CLAIMS | | | |
|--|---|----------------------------|--|--|------------------------------|---------------|
| Power Voltage | 10.2 | W | Manufacturer Power | 10.0 | W | |
| Current | 0.10 | V AC | Manufacturer Voltage | 120 | V | |
| Power Factor | 0.87 | ^ | | | | |
| Light Output | 596 | lm | Manufacturer Light Output | | | |
| Efficacy CCT | 58.5 | lm/W | Manufacturer Efficacy | 575.0 | lm | |
| CRI | 2776 | K | Manufacturer CCT | 55.0 | lm/W | |
| | 93 | | Manufacturer CRI | 2700 | K | |
| Duv | 0.000 | | - Cit | 90 | | |
| CBCP | 322 | candela | | | | 92 Lighting |
| Beam Angle Field Angle | 83 | degrees | Manufacturer CBCP | | | Facts |
| ricid Arigie | 130 | degrees | Manufacturer Beam Angle | 328 | candela | |
| | | 3.400 | - gic | | | |
| | | | | | degrees | |
| Manufacturer Li | ife | ADDITIONAL | MANUFACTURER DESCRIPTION | | | |
| Manufacturer Li | ife | ADDITIONAL | MANUFACTURER DESCRIPT | IONS OF PRO | | |
| Manufacture | ife quivalency Cla | ADDITIONAL | MANUFACTURER DESCRIPT *Designed to last 50,000 below: | IONS OF PRO | | |
| Manufacturer E Manufacturer L Lamp Description | uminaire Effici | ADDITIONAL aim ency | "Designed to last 50,000 ho hours3 year warranty" on | IONS OF PRO | | |
| Manufacturer E Manufacturer L Lamp Description | uminaire Effici | ADDITIONAL aim ency | "Designed to last 50,000 ho hours3 year warranty" on "65 Watt Equivalent Bulb" or | IONS OF PRO | | shoot as |
| Manufacturer E Manufacturer L Lamp Description Lamp Performation | uminaire Effici on nce | ADDITIONAL aim ency | nours3 year warranty" on "65 Watt Equivalent Bulb" o | urs Five Year W | | sheet "35,000 |
| Manufacturer E Manufacturer L Lamp Description Lamp Performan Driver-Ballast D | uminaire Effici on nce Description | ADDITIONAL aim ency | nours3 year warranty" on "65 Watt Equivalent Bulb" o | urs Five Year W | | Sheet "35,000 |
| Manufacturer E Manufacturer L Lamp Descriptio Lamp Performat Driver-Ballast D Ballast Factor Other Manufacturer E | uminaire Effici on nce Description | ADDITIONAL main ency | "Designed to last 50,000 ho hours3 year warranty" on "65 Watt Equivalent Bulb" or "Cree TrueWhite Technology | urs Five Year W | | Sheet "35,000 |
| Manufacturer E Manufacturer L Lamp Descriptio Lamp Performal Driver-Ballone | uminaire Effici on nce Description | ADDITIONAL aim ency | "65 Watt Equivalent Bulb" or | urs Five Year W box ⁿ packaging y" | ODUCT /arranty" on spec s | Sheet "35,000 |
| Manufacturer E Manufacturer L Lamp Descriptio Lamp Performal Driver-Ballast D Ballast Factor Other Manuf | uminaire Effici on nce Description | ADDITIONAL aim ency | nours3 year warranty" on "65 Watt Equivalent Bulb" o | urs Five Year W box ⁿ packaging y" | ODUCT /arranty" on spec s | sheet "35,000 |

Questions?

Ruth Taylor ruth.taylor@pnnl.gov